

SELF-TAPPING
SCREWSSELF-DRILLING
SCREWSTAP-FIX® THREAD
ROLLING SCREWSROLLED THREAD
MACHINE SCREWSTAMPER PROOF
SECURITY SCREWSHAMMER DRIVE
SCREWSSCREWS FOR
PLASTICSMICRO DIAMETER
SCREWSK-SERIES®
SETZMUTTERNRIVET BUSHES &
SELF-CLINCHING
FASTENERS

CD WELD STUDS

BRASS INSERTS
FOR PLASTICS

TECHNICAL DATA



LANCASTER

METRIC

Thread Rolling Screws

FOR PLASTICS


PLAS-FIX® 45°

T-Drive® (6-Lobe) Countersunk

Steel / Zinc Plated (CR3)

Steel / Black (CR3)

RoHS 2 Compliant



All images are copyright protected

Further technical data is available on page 198

Dia. max	-	-	2.5	3	3.5	4	5	-	Dia. max
Dia. C max	-	-	2.55	3.05	3.55	4.06	5.06	-	Dia. C max
d1 - max	-	-	4.40	5.50	6.30	7.35	8.40	-	d1 - max
k - ref	-	-	1.30	1.50	1.65	1.90	2.20	-	k - ref
s - A/F	-	-	-	-	-	-	-	-	s - A/F
Recess	-	-	T6	T8	T10	T15	T20	-	Recess
L- Length mm	Bulk Carton Quantity Small Box Quantity Weight (KG) per 1,000								L- Length mm
4									4
5									5
6			125,000 1,000 0.16	75,000 1,000 0.29	50,000 1,000 0.36				6
7									7
8			100,000 1,000 0.19	60,000 1,000 0.33		28,000 1,000 0.69			8
10			80,000 1,000 0.23	50,000 1,000 0.39	35,000 1,000 0.53	24,000 1,000 0.80	17,000 1,000 1.18		10
12				45,000 1,000 0.47	30,000 1,000 0.60	20,000 1,000 0.92	13,000 1,000 1.36		12
16					25,000 1,000 0.74	16,000 1,000 1.14	10,000 1,000 1.73		16
20					18,000 1,000 0.90	12,000 1,000 1.39	8,000 1,000 2.08		20
25						10,000 1,000 1.67	8,000 1,000 2.53		25
30									30
35									35
-									-
-									-
-									-
-									-
-									-

Zinc Plated (CR3) - preferred and available from stock.
 Black (CR3) - non preferred and may be subject to a lead time and MOQ.

Zinc Plated (CR3) & Black (CR3) preferred and available from stock.

See Page 219 for further detail.

PRODUCT CODE EXAMPLE

PT45WTXCSK25006ZC
PT45WTXCSK50010ZN

PRODUCT DESCRIPTION EXAMPLE

2.5 x 6 T-Drive® Countersunk Plas-Fix® 45° Screw Steel / Zinc Plated (CR3)
5 x 10 T-Drive® Countersunk Plas-Fix® 45° Screw Steel / Black (CR3)

Plas-Fix® and T-Drive® are registered trade marks of Lancaster Fastener Co Ltd
E. & O. E.
© 2018, Lancaster Fastener Co Ltd.

114

t: +44 (0) 1524 389 232

f: +44 (0) 1524 66367

enquiries@lancasterfastener.co.uk

www.lancasterfastener.com