



LANCASTER

WOOD TO STEEL APPLICATIONS

Self-Drilling Screws


WITH WINGS AND UNDERHEAD RIBS

Cross Recess (H) Ribbed Countersunk

Steel / Zinc Plated (CR3)

Steel / Black (CR3)

RoHS 2 Compliant



All images are copyright protected

Further technical data is available on page 189

Dia. mm	4.2	4.8	5.5	6.3	-	-	-	-	Dia. mm
Dia. Gauge	8	10	12	14	-	-	-	-	Dia. Gauge
d1 - max	8.10	9.50	10.80	12.40	-	-	-	-	d1 - max
k - nom	2.50	3.00	3.40	3.80	-	-	-	-	k - nom
s - A/F	-	-	-	-	-	-	-	-	s - A/F
Recess	2	2	3	3	-	-	-	-	Recess
L- Length mm	Bulk Carton Quantity Small Box Quantity Weight (KG) per 1,000								L- Length mm
32	7,000 1,000 2.44	5,500 500 3.03							32
38	5,500 500 2.92	5,000 500 3.35	2,600 250 4.70						38
45			2,000 250 6.52						45
50	2,600 500 3.76	2,500 250 4.11	1,900 250 7.52	1,600 250 9.03					50
55			1,500 250 8.05	1,500 200 9.98					55
60			1,500 250 8.58	1,500 200 10.93					60
70				1,100 125 12.24					70
80									80
90				600 100 16.82					90
-									-
-									-
-									-
-									-
-									-
-									-
-									-

Zinc Plated (CR3) - preferred and available from stock.
Black (CR3) - non preferred and may be subject to a lead time and MOQ.

See Page 219 for further details.

PRODUCT CODE EXAMPLE

DFDP3PTHCSK6390ZC
DFDP3PTHCSK5550ZN

PRODUCT DESCRIPTION EXAMPLE

6.3 x 90.0 Cross Recess (H) Ribbed Countersunk Self-Drilling Screw Steel / Zinc Plated (CR3)
5.5 x 50.0 Cross Recess (H) Ribbed Countersunk Self-Drilling Screw Steel / Black (CR3)

E. & O. E.
© 2018, Lancaster Fastener Co Ltd

t: +44 (0) 1524 389 232

f: +44 (0) 1524 66367

enquiries@lancasterfastener.co.uk

www.lancasterfastener.com

37

TECHNICAL DATA

BRASS INSERTS FOR PLASTICS

CD WELD STUDS

RIVET BUSHES & SELF-CLIMBING FASTENERS

K-SERIES® SETZMUTTERN

MICRO DIAMETER SCREWS

SCREWS FOR PLASTICS

HAMMER DRIVE SCREWS

TAMPER PROOF SECURITY SCREWS

ROLLED THREAD MACHINE SCREWS

TAP-FIX® THREAD ROLLING SCREWS

SELF-DRILLING SCREWS

SELF-TAPPING SCREWS